President

SAFETY DATA SHEET

1. Identification

Product identifier Aurora Hand Glaze

Other means of identification

Product Code 1302

Recommended use Compound, Polishing Creme

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Presta Products
Address 361 Fairview Ave
Barberton, OH 44203

United States

Telephone Phone 800-253-2526

Fax 330-777-8317

Website www.prestaproducts.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4

Health hazards Acute toxicity, oral Category 5

Acute toxicity, inhalation Category 5
Serious eye damage/eye irritation Category 2
Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if

inhaled. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash

thoroughly after handling. Wear protective gloves/eye protection/face protection.

Response IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of

fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Aurora Hand Glaze SDS US

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propan-2-ol (Isopropyl Alcohol)		67-63-0	5 - < 10
Distillates (Petroleum), Hydrotreated Light		64742-47-8	3 - < 5
Glycerol		56-81-5	3 - < 5
KEROSENE		8008-20-6	3 - < 5
Solvent Naphtha (Petroleum), Medium Aliph.		64742-88-7	3 - < 5
D-limonene Untreated		5989-27-5	1 - < 3
"1,3-Bis(hydroxymethyl)-5,5-dimeth ylimidazolidine-2,4-dione"		6440-58-0	< 0.2
Other components below reportable	levels		70 - < 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred Most important vision. Prolonged exposure may cause chronic effects. symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Ingestion

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Aurora Hand Glaze SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Glycerol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)	PEL	980 mg/m3	
, ,		400 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.
Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)	STEL	400 ppm	
, ,	TWA	200 ppm	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Туре	Value	
KEROSENE (CAS 8008-20-6)	TWA	100 mg/m3	
Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	

Avoid discharge into drains, water courses or onto the ground.

Biological limit values

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)	40 mg/l	Acetone	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

Material name: Aurora Hand Glaze sps us

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Cream.
Physical state Liquid.
Form Liquid.
Color Green.
Odor Melon

Odor threshold Not available.

pH 8.5

Melting point/freezing point -71.56 °F (-57.53 °C) estimated Initial boiling point and boiling 323.02 °F (161.68 °C) estimated

range

Flash point 145.0 °F (62.8 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.7 % estimated

(%)

Flammability limit - upper

9 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 4.83 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 633.11 °F (333.95 °C) estimated

Decomposition temperatureNot available.Viscosity4750 cPViscosity temperature68 °F (20 °C)

Other information

Density 8.20 lbs/gal
Explosive properties Not explosive.

Flammability class Combustible IIIA estimated

Material name: Aurora Hand Glaze

SDS US

1302 Version #: 03 Revision date: 06-19-2015 Issue date: 05-19-2015

Kinematic viscosity 4829.1314 cSt Kinematic viscosity 68 °F (20 °C)

temperature

Oxidizing properties Not oxidizing.

VOC (Weight %) 11.2 % w/w By Weight

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

resetions

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Isocyanates. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled. May cause damage to organs through prolonged or repeated exposure

by inhalation.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity May be harmful if swallowed. May be harmful if inhaled.

Components Species Test Results

"1,3-Bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione" (CAS 6440-58-0)

Oral

LD50 Rat 2 g/kg

D-limonene Untreated (CAS 5989-27-5)

Acute Oral

LD50 Mouse 5600 - 6600 mg/kg

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

Acute Oral

LD50 Mouse 4.5 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Respiratory or skin sensitization Respiratory sensitization

irritation

Not a respiratory sensitizer.

Causes serious eye irritation.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Material name: Aurora Hand Glaze

^{*} Estimates for product may be based on additional component data not shown.

IARC Monographs. Overall Evaluation of Carcinogenicity

D-limonene Untreated (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Not an aspiration hazard. Aspiration hazard

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8) **Aquatic** Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours (Oncorhynchus mykiss) D-limonene Untreated (CAS 5989-27-5) Aquatic Crustacea EC50 Water flea (Daphnia pulex) 69.6 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Glycerol (CAS 56-81-5)

Aquatic

Fish LC50 51000 - 57000 mg/l, 96 hours Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

D-limonene Untreated 4.232 Glycerol -1.76Propan-2-ol (Isopropyl Alcohol) 0.05

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: Aurora Hand Glaze SDS US

^{*} Estimates for product may be based on additional component data not shown.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

KEROSENE (CAS 8008-20-6)

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

US. Massachusetts RTK - Substance List

Glycerol (CAS 56-81-5)

KEROSENE (CAS 8008-20-6)

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

Material name: Aurora Hand Glaze SDS US

US. New Jersey Worker and Community Right-to-Know Act

Glycerol (CAS 56-81-5) KEROSENE (CAS 8008-20-6)

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Glycerol (CAS 56-81-5) KEROSENE (CAS 8008-20-6)

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

US. Rhode Island RTK

Propan-2-ol (Isopropyl Alcohol) (CAS 67-63-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Australian Inventory of Chemical Substances (AICS)

International Inventories

Australia

Canada

Canada

Country(s) or region

China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Inventory name

Domestic Substances List (DSL)

Non-Domestic Substances List (NDSL)

05-19-2015 Issue date 06-19-2015 Revision date

Version # 03

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use. The information in the sheet was written based on the best

knowledge and experience currently available.

Revision Information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Aurora Hand Glaze SDS US

On inventory (yes/no)*

No

No

Nο

No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).