



SAFETY DATA SHEET

1. Identification

Product identifier EPIC Hydrosheet Graphene Wash & Wax

Other means of identification

Product Code 2609

Recommended use Vehicle Wash and Wax

Recommended restrictions Not available.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.

Address 361 Fairview Ave
Barberton, OH 44203
United States

Telephone Phone 800-253-2526

Fax 330-753-2025

Website www.malcopro.com

E-mail msdsinfo@malcopro.com

Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2B

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word Warning

Hazard statement Causes eye irritation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 7.9% of the mixture consists of component(s) of unknown acute dermal toxicity. 7.9% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-[3-(dodecanoylamino)propyl-dimethylazaninium]acetate		61789-40-0	3 - < 5
N,N-dimethyldodecan-1-amine oxide		1643-20-5	3 - < 5
Distillates (Petroleum), Hydrotreated Light		64742-47-8	1 - < 3
Ethylene Glycol Monobutyl Ether		111-76-2	< 1

Chemical name	Common name and synonyms	CAS number	%
propane-1,2,3-triol		56-81-5	< 1
1-[2-[2-hydroxy-3-(propylamino)propoxy]phenyl]-3-phenylpropan-1-one		8002-74-2	< 0.1
Edge Functional Graphene		7782-42-5	< 0.1
ethane-1,2-diol		107-21-1	< 0.1
propane-1,2-diol		57-55-6	< 0.1
Other components below reportable levels			90 - 100

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	PEL	240 mg/m ³	
		50 ppm	
propane-1,2,3-triol (CAS 56-81-5)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Edge Functional Graphene (CAS 7782-42-5)	TWA	15 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1-[2-[2-hydroxy-3-(propylamino)propoxy]phenyl]-3-phenylpropan-1-one (CAS 8002-74-2)	TWA	2 mg/m ³	Fume.
Edge Functional Graphene (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
ethane-1,2-diol (CAS 107-21-1)	STEL	10 mg/m ³	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	TWA	20 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1-[2-[2-hydroxy-3-(propylamino)propoxy]phenyl]-3-phenylpropan-1-one (CAS 8002-74-2)	TWA	2 mg/m ³	Fume.
Edge Functional Graphene (CAS 7782-42-5)	TWA	2.5 mg/m ³	Respirable.
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	TWA	24 mg/m ³	
		5 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
propane-1,2-diol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol.

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection** Not available.**Skin protection****Hand protection** Not available.**Other** Not available.**Respiratory protection** Not available.**Thermal hazards** Not applicable.

General hygiene considerations Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance** Clear.**Physical state** Liquid.**Form** Liquid.**Color** Charcoal gray**Odor** Faint chemical**Odor threshold** Not available.**pH** 6 - 8**Melting point/freezing point** Not available.**Initial boiling point and boiling range** Not available.**Flash point** >200 C**Evaporation rate** Not available.**Flammability (solid, gas)** Not applicable.**Upper/lower flammability or explosive limits****Explosive limit - lower (%)** Not available.**Explosive limit - upper (%)** Not available.**Vapor pressure** -0.01 hPa estimated**Vapor density** Not available.**Relative density** Not available.**Solubility(ies)****Solubility (water)** Not available.**Partition coefficient (n-octanol/water)** Not available.**Auto-ignition temperature** Not available.**Decomposition temperature** Not available.**Viscosity** 350 - 700 cP @ 20 C**Other information****Density** 8.34 - 8.44 lb/gal**Explosive properties** Not explosive.**Flammability** not flammable**Oxidizing properties** Not oxidizing.**VOC** 0.02 % 1:128 dilution required

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
ethane-1,2-diol (CAS 107-21-1)		
Acute		
Dermal		
LD50	Rabbit	9530 mg/kg
Oral		
LD50	Rat	5.89 g/kg
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)		
Acute		
Dermal		
LD50	Rabbit	400 mg/kg
Oral		
LD50	Rat	560 mg/kg
propane-1,2,3-triol (CAS 56-81-5)		
Acute		
Inhalation		
LC50	-	> 570 mg/m ³ , 1 Hours
propane-1,2-diol (CAS 57-55-6)		
Acute		
Oral		
LD50	Rat	30 g/kg

Skin corrosion/irritation Not available.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutyl Ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity	Not available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours
ethane-1,2-diol (CAS 107-21-1)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 8050 mg/l, 96 hours
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours
propane-1,2,3-triol (CAS 56-81-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) >= 51000 - <= 57000 mg/l, 96 hours
propane-1,2-diol (CAS 57-55-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential**Partition coefficient n-octanol / water (log Kow)**

ethane-1,2-diol	-1.36
Ethylene Glycol Monobutyl Ether	0.83
N,N-dimethyldodecan-1-amine oxide	4.67
propane-1,2,3-triol	-1.76
propane-1,2-diol	-0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**DOT**

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ethane-1,2-diol (CAS 107-21-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Serious eye damage or eye irritation
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ethane-1,2-diol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

propane-1,2,3-triol (CAS 56-81-5) Other Flavoring Substances with OSHA PEL's

US state regulations**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

ethane-1,2-diol (CAS 107-21-1)
Ethylene Glycol Monobutyl Ether (CAS 111-76-2)

California Proposition 65

WARNING: WARNING: Cancer - www.P65Warnings.ca.gov For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-04-2022

Version # 01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.