

MALCO[®] EPIC[®] PRO CERAMIC COATING (#109330)

DESCRIPTION

EPIC[®] PRO Ceramic Coating is designed to produce the ultimate vehicle finish. This specially formulated coating provides 3 years (or 36,000 miles) of protection, along with the industry's highest gloss finish. It bonds with the clear coat to create a durable, hydrophobic surface that prevents dirt, water spots, and other contaminants from adhering to paint. Apply EPIC[®] PRO Ceramic Coating to your vehicle for the ultimate "wet" look. The optimum viscosity of this unique formula simplifies application. However, professional installation of EPIC[®] PRO Ceramic Coating and the EPIC[®] Ceramic Coating System is recommended.

DIRECTIONS

EPIC[®] PRO Ceramic Coating requires a clean, smooth surface for proper adhesion. Wash, clay bar, and machine polish your vehicle prior to application. We recommend washing with EPIC[®] Ceramic Prep Wash Concentrate and correcting paint imperfections with the EPIC[®] Paint Correction System. If you cannot achieve a professional level of cleaning and paint correction on your own, please seek professional help. Ensure the vehicle is at room temperature (50°F - 75°F). Only apply the product in a covered, dust-free garage and allow the vehicle to remain inside for at least 24 hours afterward. For maximum results:

- Put on a pair of rubber gloves for protection. Shake product well prior to use.
- Clean and prep your surface with EPIC[®] Ceramic Final Prep Wipe, using a lint-free cloth.
- Wrap a Suede Cloth around the Applicator Pad. Apply 3-4 drops of EPIC[®] PRO Ceramic Coating to the cloth, and immediately reseal the product.
- Apply coating to surface in a crosshatch pattern, using even pressure. We recommend working in a defined 20-in x 20-in area until the product is worked into the clear coat.
- Expect the coated area to rainbow or flash within 30-90 seconds of application. At this point, begin removing the product with a clean, microfiber towel. Be sure to remove any remaining residue.
- Repeat steps for coating the entire vehicle, using an overlapping technique on each section to ensure full coverage.
- Keep the vehicle in a controlled environment for at least 12 hours while keeping it dry for a minimum of 24 hours. Complete bonding with the paint can take up to seven days, so it is vital to have garage access.

FEATURES AND BENEFITS

Easy-to-apply coating	Bonds with clear coat for outstanding depth of gloss
Designed to complete the EPIC® Paint Correction and Protection System	Optimum viscosity simplifies application for experts and novices alike
Produces the ultimate “wet” look	Excellent hydrophobic properties allow water and dirt to slide right off

 **WARNING/AVERTISSEMENT/ ADVERTENCIA:** Cancer - www.P65Warnings.ca.gov

PACKAGE CONTENTS

- 1 - 30 mL Bottle of EPIC® PRO Ceramic Coating
- 1 - Applicator Pad
- 10 - Suede cloths
- 1 – EPIC® PRO Ceramic Coating Installation Decal for inner door panel
- 1 - Technical Data Sheet

PRODUCT FAQs

Q1: What should I use to apply Malco® EPIC® Pro Ceramic Coating?

A1: The suede cloth should always be used for application. These cloths are designed for one use only and should be disposed of upon completion.

Q2: How long does it take to apply EPIC® Pro Ceramic Coating?

A2: It depends on the amount of paint correction required beforehand and the experience level of the installer. You want to be sure you do not rush the application. A few hours are typical.

Q3: Is one layer of coating enough to provide protection?

A3: Yes, one layer is enough. Adding multiple layers does not necessarily increase protection.

Q4. How do I know when the coating is completely worked into the clearcoat?

A4. Work the product into the vehicle surface in a crosshatch pattern until you can no longer see any remaining product. You will feel a slight resistance building as the coating is fully worked in.