

MALCO[®] EPIC[™] CERAMIC COATING (1095)

DESCRIPTION

EPIC[™] Ceramic Coating is designed for the ultimate vehicle finish. This specially formulated coating provides years of protection and the industry's highest gloss finish. When professionally installed, the EPIC Ceramic system will bond with the vehicle's clear coat to create a durable, hydrophobic surface. This coating will prevent dirt, water spots, and contaminants from adhering to paint, therefore prolonging the life and ease of cleaning for any vehicle. Included in the EPIC Ceramic Starter kit is everything needed to complete one car or truck, including: one bottle of EPIC Ceramic Coating, Prep Wash Concentrate, Prep Wipe, Applicator Pad, Suede Applicator Cloths, and an Ultra-Soft Edgeless Microfiber Towel.

DIRECTIONS

EPIC Ceramic Coating requires a clean, smooth surface for proper installation. Malco recommends using the EPIC[™] Paint Correction System prior to ceramic application. This will ensure an ideally prepared surface, free of defects and contaminants. For best results, be sure to follow these directions.

- Use the EPIC[™] Prep Wash, and fully dry the vehicle
- Make sure the vehicle is at room temperature between 50°F - 75°F, and in a covered, dust free garage
- Use the EPIC Paint Correction System to remove any imperfections
- Double check the surface is free of defects and contaminants.
- Use the EPIC Prep Wipe with a lint free cloth to prepare right before application
- Wrap a suede cloth around the applicator pad and apply 3-4 drops of EPIC Ceramic Coating to the cloth
- Work in a controlled area, 20x20-inch square, applying the coating to the surface in a cross-hatch pattern with the applicator several times until the coating is worked into the clear coat
- Using the clean ultra-soft microfiber towel, wipe the area clean and dry of any residue, while gently buffing to a brilliant shine
- Repeat these steps for the whole vehicle, using an overlap on each section is recommended to ensure full coverage
- Keep the vehicle in a controlled environment for at least 12 hours and keep dry for minimum of 24 hours, full bond with the paint can take seven days

FEATURES AND BENEFITS

Industry's easiest-to-apply coating system	Bonds with clear coat for outstanding depth of gloss
Designed to complement the EPIC™ Paint Correction System	Optimum viscosity simplifies application for experts and novices alike
Produces the ultimate “wet” look	Excellent hydrophobic properties allow water and dirt to slide right off

PACKAGE CONTENTS

EPIC™ Ceramic Starter Kit (800215)

EPIC™ Prep Wash Concentrate (# 109608)
 EPIC™ Final Prep (# 190716)
 EPIC™ Ceramic Coating (# 02058)
 Applicator (# 801038)
 Suede cloths (# 810104)
 Ultra-soft Edgeless Microfiber Towel (# 800136)

EPIC™ Ceramic Single-Use Kit (109503)

EPIC™ Ceramic Coating (# 02058)
 Applicator (# 801038)
 Suede cloths (# 810104)

PRODUCT FAQs

Q1: What should I use to apply Malco® EPIC™ Ceramic Coating?

A1: The suede cloth should always be used for application. These cloths are designed for one use only, and should be disposed of upon completion.

Q2: How long does it take to apply EPIC Ceramic Coating?

A2: It depends on the amount of paint correction required beforehand and the experience level of the installer. You want to be sure you do not rush the application. A few hours is typical.

Q3: Is one layer of coating enough to provide protection?

A3: Yes, one layer is enough. However, multiple layers of ceramic coating will not harm the clear coat or system, and will provide even longer durability.

Q4. How do I know when the coating is completely worked into the clearcoat?

A4. Continue wiping with the suede covered applicator in a cross hatch, until you no longer see any more ‘wet’ coating. You will feel a slight resistance as the coating is fully worked in.